

## Technical Specifications for Vertical Double Skin Air Handling Units

AHU Models	AHU Overall Dimensions			Coil Details		Air Quantity		Motor Rating		Pre-Filter (50 mm thick)		Operating Weight (kg)	
	Length	Width	Height	Fin Length	Fin Height			12 mm E SP	20 mm E SP	Size	Quantity	With 4-Row Deep	With 6 - Row Deep
	mm	mm	mm	mm	mm	CFM	CMH	kW	kW	W-mm x H-mm	Nos.	Kg	Kg
CAWV - 035	730	1032	1312	762	508	2083	3541	0.75	1.1	600 x 300	2	190	205
CAWV - 050	780	1388	1378	1118	508	3056	5195	1.1	1.5	600 x 500	2	225	245
CAWV - 070	830	1591	1519	1321	572	4063	6907	1.5	2.2	500x600, 400 x 600	1 # Each	330	360
CAWV - 100	980	1763	1826	1473	762	6042	10271	2.2	3.7	500 x 400	6	395	435
CAWV - 140	830	2220	1869	1930	762	7917	13459	3.7	3.7	500 x 400	8	470	520
CAWV - 170	980	2728	1986	2692	699	10000	17000	3.7	5.5	600 x 400	8	560	610
CAWV - 200	980	2932	2050	2642	826	11736	19951	5.5	5.5	600x400, 500x400	4 & 6	590	650
CAWV - 250	1041	2932	2276	2642	1016	14444	24555	5.5	7.5	600x500, 500x500	4 & 6	670	745
CAWV - 270	1132	3124	2534	2794	1080	16233	27596	5.5	7.5	600 x 500	10	760	840
CAWV - 300	1132	3226	2597	2896	1143	17813	30282	7.5	7.5	600x500 & 600x600	5 # Each	810	885